



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 0 936 183 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
18.08.1999 Bulletin 1999/33

(51) Int. Cl.<sup>6</sup>: **C01B 3/38**

(21) Application number: 99102386.2

(22) Date of filing: 08.02.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(30) Priority: 17.02.1998 DK 21698

(71) Applicant: Haldor Topsoe A/S  
DK-2800 Lyngby (DK)

(72) Inventors:  
• Christensen, Peter Seier  
2400 Copenhagen NV (DK)  
• Christensen, Thomas Sandahl  
2800 Lyngby (DK)  
• Primdahl, Ivar Ivarsen  
2400 Copenhagen NV (DK)

(54) **Process for the autothermal reforming of a hydrocarbon feedstock**

(57) Process for the soot free autothermal steam reforming of a hydrocarbon feedstock by autothermally reforming the feedstock in an autothermal reactor at a given temperature and a given steam to carbon ratio in the feedstock and operating at a pressure in the reactor being above a critical value, where no soot is present in the steam reformed feedstock.

EP 0 936 183 A2

## Description

## BACKGROUND OF THE INVENTION

- 5 [0001] The present invention is directed to soot free autothermal reforming (ATR) of hydrocarbon feed.
- [0002] In the autothermal reforming, combustion of hydrocarbon feed is carried out with substoichiometric amounts of oxygen by flame reactions in a burner combustion zone and, subsequently, steam reforming of the partially combusted feedstock in a fixed bed of steam reforming catalyst. Substoichiometric combustion of hydrocarbons leads disadvantageously to formation of soot. Soot formation may be avoided by using a specific burner design and through  
 10 controlling the operating conditions of the ATR process. Soot is formed in the flame of an autothermal reactor within certain ranges of operating conditions. When the amount of steam relative to the other components sent to the ATR reactor is under a critical value, soot is formed in the reacting feed. The design of the burner nozzles has influence on the critical steam to carbon ratio. One such burner useful in ATR is described in US Patent No. 5,496,170. The limiting amount of steam can be expressed as the critical steam to carbon ratio, which is the molar feed flow rate of steam to  
 15 the molar flow rate of carbon in the hydrocarbon feed. The hydrocarbon feedstocks can be in form of natural gas or another kind of hydrocarbon including LPG, butane, naphtha, etc. The molar flow rate of carbon is calculated as the molar flow rate of the hydrocarbon times the carbon contents of the hydrocarbon.
- [0003] Examples of operation conditions, which do not result in soot formation, are summarized in a paper by Christensen and Primdahl (Hydrocarbon processing, March 1994, pages 39-46). Those conditions are shown in Table 1. The  
 20 tests have been conducted in a pilot plant. Due to heat loss from the relatively small pilot unit, the adiabatic ATR exit temperature will be higher than the measured ATR exit temperature. This means that if a large unit, from which the heat loss is negligible, is subjected to the exact same operating conditions, the ATR exit temperature will be close to the adiabatic ATR exit temperature. The soot precursors are formed in the combustion zone of the ATR. Most of the heat loss occurs after the combustion zone. A subsequent heat loss cannot have any influence on the reactions in the combustion zone. The oxygen to carbon ratio ( $O_2/C$ ) is also shown in Table 1. The definition of this ratio is analogue to the steam to  
 25 carbon ratio, however, with steam substituted by oxygen. The exit temperature from the ATR reactor can be calculated from the  $O_2/C$  ratio, when the heat loss from the reactor is known.

Table 1

Case No.	Oxygen to Carbon Ratio	$H_2O/C$	$CO_2/C$	Measured ATR Exit Temp. °C	Adiabatic ATR Exit Temp. °C
A	0.60	1.43	0	950	1013
B	0.62	0.59	0	1065	1173
C	0.60	0.86	0	1000	1073
D	0.67	0.68	0.47	1018	1147
E	0.70	0.67	0.75	1030	1147
F	0.73	0.58	0.98	1028	1177
Operation conditions which do not result in soot formation (from Christensen and Primdahl, 1994)					

- 45 [0004] Advantageously, the process is operated at low steam to carbon ratios, since a low ratio lowers the investment expenses for an ATR plant and reduces the necessary energy consumption in operating the plant. Additionally, a low steam to carbon ratio makes it possible to optimize the produced synthesis gas composition for production of CO-rich gases for e.g. methanol or dimethyl ether synthesis and Fischer-Tropsch processes.
- [0005] It has been found that the operating pressure has a very strong influence of the critical steam to carbon ratio.
- 50 [0006] It has further been found that at a given temperature and steam to carbon ratio in the feedstock, the feedstock is autothermally reformed without formation of detrimental soot when adjusting the operation pressure in the autothermal reactor above a critical value.

## DESCRIPTION OF THE INVENTION

- 55 [0007] Accordingly, this invention is a process for the soot free autothermal reforming of a hydrocarbon feedstock in an autothermal reactor at a given temperature and a given steam to carbon ratio in the feedstock and adjusting operation pressure in the reactor above a critical value, so that no soot is present in the steam reformed feedstock.

[0008] The critical steam to carbon ratio decreases when the operating pressure is increased. By means of the invention, the operating pressure in the ATR reactor is the critical parameter for suppressing soot formation. By increasing the operating pressure, it is possible to operate advantageously at a lower steam to carbon ratio.

[0009] The actual critical pressure will depend on the burner design used in the ATR reactor.

5 [0010] Preferably, the pressure is adjusted to meet the following relation between steam carbon ratio, temperature at exit of the reactor and pressure:  $p \geq 15.0 - 0.00914 T_{\text{exit}} - 1.92 \cdot S/C$  or at adiabatic conditions  $p \geq 13.4 - 0.00753 \cdot T_{\text{adiabatic}} - 1.74 S/C$ , where  $p$  is the pressure in MPa,  $T$  is the gas temperature in K at exit of the reactor or at adiabatic conditions, respectively,  $S/C$  is the molar steam-to-carbon ratio in the feedgas.

10 [0011] The invention has been tested in the pressure range of 0.86-2.95 MPa. However, it is apparent from the following examples that the invention will be applicable at higher operating pressures.

#### Example 1

15 [0012] The test unit consists of a system for providing the feeds to the ATR reactor, the ATR reactor itself, and equipment for posttreatment of the product gas.

20 [0013] The feed streams consist of natural gas, steam, oxygen and hydrogen. All gases are compressed to the operating pressure and preheated to the operating temperature. The natural gas is desulphurized before entering the ATR reactor. The feeds were combined into two streams and were sent to the burner of the ATR. The burner used in the example is described in U.S. Patent No. 5,496,170, which by reference is included herein. One feed stream contained natural gas, hydrogen and steam. This feed stream was heated to 500°C. The other feed stream contained oxygen and steam. This feed stream was heated to 220°C.

[0014] In the ATR reactor, the substoichiometric combustion and subsequent catalytic steam reforming and shift reactions are carried out. The inlet and exit gas compositions are measured by gaschromatography. The product gas is in equilibrium with respect to the reforming and shift reactions.

25 [0015] Downstream the ATR reactor, the process gas is cooled down and the majority of the steam content in the product gas is condensed. If soot is formed, it is captured in the condensate. The condensate was subjected to both gravimetric and spectrophotometric examinations.

[0016] The following tests were carried out to demonstrate the influence of operating pressure on the critical steam to carbon ratio. The hydrocarbon used was natural gas. The composition of the natural gas is given in Table 2.

30

Table 2

35

40

45

Composition of Natural Gas	
Component	Mole Fraction %
N <sub>2</sub>	0.45
CO <sub>2</sub>	1.20
CH <sub>4</sub>	95.36
C <sub>2</sub> H <sub>6</sub>	2.22
C <sub>3</sub> H <sub>8</sub>	0.45
C <sub>4</sub> H <sub>10</sub>	0.23
C <sub>5</sub> H <sub>12</sub> and higher hydrocarbons	0.08

[0017] Each test was made by approaching the critical steam to carbon ratio from the steam rich side. The tests were initiated with a sufficiently high steam flow to ensure soot free conditions. The steam flow was then decreased in steps which resulted in a decrease in the steam to carbon ratio of approximately 0.03. The system was allowed to become stable after which the condensate was examined for soot content. If the condensate was still soot free, the next step was taken. The term "soot free conditions" refers to condition in which the soot formation is negligible. The soot amount formed at the critical steam to carbon ratio was approximately 3-5 ppm.

50 [0018] The critical steam to carbon ratio as function of pressure measured at two different operating temperatures is given in Table 3. The flow rates were in all tests 100 Nm<sup>3</sup>/h natural gas and 3 Nm<sup>3</sup>/h hydrogen. 100 Nm<sup>3</sup>/h natural gas correspond to a carbon flow rate of 102.5 Nm<sup>3</sup>/h. The steam flow was adjusted to obtain the given steam to carbon ratio. The oxygen flow rate was adjusted to obtain the desired operating temperature and varied in the range 55-62 Nm<sup>3</sup>/h.

[0019] Due to heat loss from the relatively small pilot unit, the adiabatic ATR exit temperature will be higher than the

temperature given in Table 2. A large industrial unit will be very close to adiabatic and the exit temperature from such a unit will, hence, be very close to the adiabatic given in Table 3 when the industrial unit otherwise is operated at exactly the same conditions as quoted in Table 3.

Table 3

Test No.	Oxygen to Carbon Ratio	Pressure MPa	Measured ATR Exit Temp. °C	Adiabatic ATR Exit Temp. °C	Critical Steam to Carbon Ratio
1.1	0.58	1.91	960	1041	0.96
1.2	0.57	2.16	960	1026	0.78
1.3	0.56	2.46	960	1039	0.62
1.4	0.54	2.75	960	1014	0.50
1.5	0.60	1.77	1035	1113	0.68
1.6	0.58	2.06	1035	1103	0.39
1.7	0.57	2.46	1035	1110	0.27
1.8	0.55	2.95	1035	1104	0.15

Critical steam to carbon ratio as function of pressure and operating temperature.

[0020] The composition of the product gas from the ATR reactor in the tests of Table 3 was measured by gaschromatography. Selected gas compositions are shown in Table 4. The gas composition is given as dry mole%, which is the mole composition of the gas components, when steam is not included.

Table 4

Composition of Product Gas (dry mole%) of the Tests of Table 3					
Test Number	H <sub>2</sub>	N <sub>2</sub>	CO	CO <sub>2</sub>	CH <sub>4</sub>
	%	%	%	%	%
1.1	65.2	0.21	25.7	7.91	0.89
1.4	63.0	0.25	28.0	5.50	3.26
1.5	65.2	0.24	27.7	6.49	0.87
1.7	64.0	0.22	30.7	3.80	1.31

[0021] A very strong dependence of the critical steam to carbon ratio is seen for both operating temperatures. At an operating temperature of 1035°C, the critical steam to carbon ratio decreases by a factor 4.5, when the pressure is increased by less than a factor 2.

[0022] The data disclosed in Table 3 correlate with the relationship  $p = 15.0 - 0.00914 T_{\text{exit}}^{-1.92} \text{ S/C}$ , where T is the


temperature at exit of the reactor in K and the pressure in MPa.

[0023] From the above equation it is calculated that at a pressure above 3.5 MPa and a temperature at exit of the reactor above 985°C, the critical steam to carbon ratio is zero.

[0024] The data in Table 3 correlate with the relationship  $p = 13.4 - 0.00753 \cdot T_{\text{adiabatic}} - 1.74 \text{ S/C}$ , where T is the adiabatic exit temperature in K. From this equation it is calculated that at a pressure above 3.5 MPa and an adiabatic temperature above 1042°C, the critical steam to carbon ratio is zero.

#### Claims

1. Process for the soot free steam reforming of a hydrocarbon feedstock by autothermally reforming the feedstock in an autothermal reactor at a given temperature and a given steam to carbon ratio in the feedstock and operating at a pressure in the reactor being above a critical value, where no soot is present in the steam reformed feedstock.
2. Process according to claim 1, wherein the operation pressure is adjusted to a value of  $p \geq 13.4 - 0.00753 \cdot T_{\text{adiabatic}} - 1.74 \text{ S/C}$ , where
  - p is the pressure in MPa,
  - T is the adiabatic gas temperature in K of the reformed feedstock, and
  - S/C is the molar steam-to-carbon ratio in the feedstock.
3. Process according to claim 1, wherein the operation pressure is adjusted to a value of  $P \geq 15.0 - 0.00914 T_{\text{exit}} - 1.92 \cdot \text{S/C}$ , where
  - p is the pressure in MPa,
  - T is the gas temperature in K of the reformed feedstock at outlet of the reactor, and
  - S/C is the molar steam-to-carbon ratio in the feedstock.
4. Process according to claim 1, wherein the operating pressure is above 2.9 MPa.
5. Process according to claim 1, wherein the operating pressure is above 3.5 MPa.
6. Process according to claim 1, wherein the operating pressure is above 3.5 MPa and the adiabatic temperature of the autothermally reformed feedstock is above 1042°C and steam to carbon ratio in the feedstock  $\geq 0$ .



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) **EP 0 936 183 A3**

(12)

**EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:  
23.02.2000 Bulletin 2000/08

(51) Int. Cl.<sup>7</sup>: **C01B 3/38**

(43) Date of publication A2:  
18.08.1999 Bulletin 1999/33

(21) Application number: 99102386.2

(22) Date of filing: 08.02.1999

(84) Designated Contracting States:  
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE  
Designated Extension States:  
AL LT LV MK RO SI

(30) Priority: 17.02.1998 DK 21698

(71) Applicant: Haldor Topsoe A/S  
DK-2800 Lyngby (DK)

(72) Inventors:

- Christensen, Peter Seier  
2400 Copenhagen NV (DK)
- Christensen, Thomas Sandahl  
2800 Lyngby (DK)
- Primdahl, Ivar Ivarsen  
2400 Copenhagen NV (DK)

(54) **Process for the autothermal reforming of a hydrocarbon feedstock**

(57) Process for the soot free autothermal steam reforming of a hydrocarbon feedstock by autothermally reforming the feedstock in an autothermal reactor at a given temperature and a given steam to carbon ratio in the feedstock and operating at a pressure in the reactor being above a critical value, where no soot is present in the steam reformed feedstock.

EP 0 936 183 A3



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 99 10 2386

DOCUMENTS CONSIDERED TO BE RELEVANT			Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
Category	Citation of document with indication, where appropriate, of relevant passages			
X	GB 2 257 981 A (INST FRANCAIS DU PETROL) 27 January 1993 (1993-01-27) * page 2, line 21 - page 4, line 25 * * example 1 *	1-5	C01B3/38	
X	US 5 628 931 A (LEDNOR PETER W ET AL) 13 May 1997 (1997-05-13) * examples *	1		
X	US 4 473 543 A (SETZER HERBERT J ET AL) 25 September 1984 (1984-09-25) * the whole document *	1		
D,X	CHRISTENSEN, T. S. ET AL: "Improve syngas production using autothermal reforming" HYDROCARBON PROCESS., INT. ED. (1994), 73(3), 39-42, 44, 46, 1994, XP002124677 * the whole document *	1		
The present search report has been drawn up for all claims				TECHNICAL FIELDS SEARCHED (Int.Cl.6)  C01B
Place of search <b>THE HAGUE</b>		Date of completion of the search <b>21 December 1999</b>	Examiner <b>Van der Poel, W</b>	
CATEGORY OF CITED DOCUMENTS			<p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons            &amp; : member of the same patent family, corresponding document</p>	
<p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p>				

EPO FORM 1503 03/82 (P04C01)

# ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 99 10 2386

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-12-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2257981 A	27-01-1993	FR 2679217 A	22-01-1993
		AU 650766 B	30-06-1994
		AU 1963392 A	21-01-1993
		NO 922819 A	19-01-1993
		US 5632787 A	27-05-1997
		US 5733514 A	31-03-1998
		ZA 9205357 A	17-01-1994
US 5628931 A	13-05-1997	AU 696238 B	03-09-1998
		AU 2484695 A	18-01-1996
		CA 2153304 A	08-01-1996
		CN 1120064 A	10-04-1996
		ZA 9505578 A	12-02-1996
US 4473543 A	25-09-1984	US 4415484 A	15-11-1983
		AU 552590 B	05-06-1986
		AU 1389783 A	03-11-1983
		BE 896502 A	16-08-1983
		BR 8302055 A	27-12-1983
		CA 1197228 A	26-11-1985
		CH 652941 A	13-12-1985
		DE 3314423 A	10-11-1983
		DK 180683 A,B,	27-10-1983
		FI 831409 A,B,	27-10-1983
		FR 2525493 A	28-10-1983
		GB 2118857 A,B	09-11-1983
		IT 1161232 B	18-03-1987
		JP 1713171 C	27-11-1992
		JP 3078137 B	12-12-1991
		JP 58196849 A	16-11-1983
		NL 8301425 A	16-11-1983
		NO 831440 A,B,	27-10-1983
		SE 452256 B	23-11-1987
		SE 8302234 A	27-10-1983
		ZA 8302671 A	28-12-1983

EPO FORM P4459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82